
TUPRESTIGE CRUSH RESISTANT



Premium grade low permeation suction and delivery hose suitable for a wide range of products. Recommended for wine and spirits. Crush resistant. Hose tested according to the main norms for food contact materials (FCM – Reg. (CE) 1935/2004). Manufactured according to GMP (Reg. (CE) 2023/2006).

DESCRIPTION

Tube

BIIR, white, phthalates free, tested in compliance with 1907/2006/CE (REACH). Meets FDA 21 CFR 177.2600; BfR XXI cat. 2; DM 21/03/1973 and subsequent amendments; REGULATION 1935/2004/CE; Japan Ministry of Health and Welfare Notice No.370,1959 and No.201,2006; 3-A RPSCQC for (62-02) Hose Assemblies; Arrêté du 05 août 2020.

Reinforcement

synthetic plies, thermoplastic wire helices

Cover

smooth, red, cloth finish. Abrasion, ageing and ozone resistant

Marking

TUDERTECHNICA TUPRESTIGE CRUSH RESISTANT

TECHNICAL CHARACTERISTICS

Temperature range : -40°C / +120°C (-40°F / +248°F)
Norm : ISO 1307 for dimensional tolerances

refer to guidelines for cleaning and sanitizing on Tudertechnica website

GMP CE 2023/2006 · PHTHALATES REACH FREE · FDA · BfR · DM 21/03/1973 · CE 1935/2004 · MHLW 1959-2006 · RPSCQC No. 72 · ARRÊTÉ FRANÇAIS 05/08/2020

Inside diameter		Outside diameter		Vacuum		Working pressure		Burst pressure		Appr. weight		Bending radius	
[mm]	*[in]*	*[mm]*	*[in]*	*[bar]*	*[psi]*	*[bar]*	*[psi]*	*[bar]*	*[psi]*	*[kg/mt]*	*[lbs/ft]*	*[mm]*	*[in]*
25	1,00	39	1,54	0,7	10	10	150	30	450	0,90	0,60	100	3,94
32	1,26	49	1,93	0,7	10	10	150	30	450	1,33	0,89	140	5,51
38	1,50	54	2,13	0,7	10	10	150	30	450	1,45	0,97	170	6,69
51	2,00	67	2,64	0,7	10	10	150	30	450	1,84	1,23	240	9,44
63,5	2,50	81,5	3,21	0,7	10	10	150	30	450	2,48	1,66	310	12,20
76	3,00	94	3,70	0,7	10	10	150	30	450	2,90	1,94	380	14,96

REV-2026-11-13

Data refer to ambient temperature (20°C). Other diameters, wall thickness, cover colours and pressure only on specific request.